MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS 1963 A

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
AFOSR-TR-80-1205	AD-A092658	

4. TITLE (and Subtitle)	5. TYPE OF REPORT & PERIOD COVERED
OPTIMAL SAMPLE DEPENDS ON OPTIMALITY CRITERION	Interim
	6. PERFORMING ORG. REPORT NUMBER

7. AUTHOR(s)	8. CONTRACT OR GRANT NUMBER(s)
Herbert Lacayo, Carlos Pereira, Frank Proschan, and Carl Sarndal	AFOSR-78-3678

9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Florida State University Department of Statistics Tallahassee, Florida 32306	61102F 2304/A5

11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
Air Force Office of Scientific Research /NM	October 1980
Bolling AFB, Washington, DC 20332	13. NUMBER OF PAGES
	6

14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)	15. SECURITY CLASS. (of this report)
	UNCLASSIFIED
	15a. DECLASSIFICATION DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Sampling, Optimal, sequential testing, Bayesian statistics

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Four different sampling procedures are compared. Each is optimal under an appropriate optimality criterion.

Optimal Sample Depends on Optimality Criterion

by

Herbert Lacayo[1], Carlos A.B. Pereira[2], Frank Proschan[1], and
Carl Särndal

Key Words: Sampling, optimal, sequential testing, Bayesian statistics.

AMS 1970 Subject Classifications: 62D05, 62N05.

Please read the following problem formulation and select among
the options listed below.

A warehouse contains N batteries in storage. Batteries fail
(silently) according to life distribution $F(t) = 1 - \exp\{-\lambda t\}$, λ known.
At time t_1 we select a random sample of size n_1 batteries and find
that f_1 are failed (and discarded immediately), while $n_1 - f_1$ are
functioning and returned to the warehouse. At time $t_2 > t_1$ we are to
select a second random sample of n_2 batteries. How shall we select our
second sample: more specifically, how many as yet untested batteries
shall we select and how many batteries tested at time t_1 shall we select?
(Of course, the total number selected must equal n_2.)

1. Select as many from among the untested batteries as possible.
   If the sample size n_2 is bigger than the number of such batteries,
   choose the remainder from among the previously (at time t_1) tested
   batteries.

2. Select as many from among the previously tested batteries as
   possible. If $n_2 > n_1 - f_1$, to complete the sample, choose the
   remainder from among the untested batteries.

3. Compute $p_1 \equiv e^{-\lambda t_2}$ and $p_2 \equiv e^{-\lambda(t_2 - t_1)}$. If p_2 is closer to
   1/2 than is p_1, use the sampling procedure described in 2. If
   p_1 is closer to 1/2 than is p_2, use the sampling procedure des-
   cribed in 1.

4. Dismiss the problem formulation as unrealistic, since who knows
   λ? Set up a Bayesian model and proceed as in 4′ below.

You guessed it - all four choices are correct. That is, there are
three reasonable optimality criteria such that for a given criterion, the

optimal procedure is described in one of the first three statements
above. The Bayesian procedure proposed in statement 4 is appropriate
for λ unknown.

Let us take the easy cases first. Suppose our goal is to maximize the number of batteries that we know are functioning at time t_2.
Then it is easy to see that we should follow Procedure 2. The probability that a battery, found to be functioning at time t_1, will be found
upon inspection at time t_2 to be functioning is $e^{-\lambda t_2}/e^{-\lambda t_1} = e^{-\lambda(t_2 - t_1)}$.
On the other hand, a previously uninspected battery has probability $e^{-\lambda t_2}$
of being in the functioning state upon inspection at time t_2. Since
$e^{-\lambda t_2} < e^{-\lambda(t_2 - t_1)}$, it follows that the optimal strategy to maximize
the number of batteries we know to be functioning at time t_2 is as described in Procedure 2.

Suppose, on the other hand, our goal is to weed out as many defective
batteries as possible by inspection. Now, the optimal plan is described
in Procedure 1. This follows from the fact that the probability that a
battery found to be functioning at time t_1, will be found upon inspection
at time t_2 to be in the failed state is $(e^{-\lambda t_1} - e^{-\lambda t_2})/e^{-\lambda t_1} = 1 - e^{-\lambda(t_1 - t_2)}$.
On the other hand, a previously uninspected battery has probability $1 - e^{-\lambda t_2}$
of being in the failed state upon inspection at time t_2. Since
$1 - e^{-\lambda t_2} > 1 - e^{-\lambda(t_2 - t_1)}$, it follows that the optimal strategy to
weed out the maximum number of defective batteries is as described in
Procedure 1.

A third possible goal is to estimate as precisely as possible - precision
is defined by the squared error loss function - the number X of functioning
batteries at time t_2 when λ is known. The problem is to select a sample

of fixed size, from among (a) the batteries already inspected at time t_1 and found to be still alive and (b) the batteries not yet inspected at time t_1.

Note that the (Bernoulli) variable used to indicate the state (functioning or not) of a battery selected from among (a) has variance $e^{-\lambda(t_2 - t_1)}(1 - e^{-\lambda(t_2 - t_1)})$, while the variable used to indicate the state of a battery selected from among (b) has variance $e^{-\lambda t_2}(1 - e^{-\lambda t_2})$. Since we wish to obtain an estimate of the number X with smallest possible risk, we simply follow procedure 3 above.

4´ Suppose that λ is unknown and we choose a distribution to represent our prior opinion about λ. In particular, suppose we choose a Gamma distribution a priori. That is,

$$\Pi(\lambda) = \frac{\beta^{\alpha}\lambda^{\alpha-1}}{\Gamma(\alpha)} e^{-\beta\lambda} \qquad (1)$$

is the prior density for λ. Having observed a sample of size n_1 at time t_1 containing f_1 failed batteries and $n_1 - f_1$ functioning batteries, we compute the posterior mean of the function:

$$p_1(1 - p) - p_2(1 - p_2) = e^{-\lambda t_2}(1 - e^{-\lambda t_2}) - e^{-\lambda(t_2-t_1)}(1 - e^{-\lambda(t_2-t_1)}) =$$
$$e^{-\lambda t_2} - e^{-2\lambda t} \qquad {}^{-\lambda(t_2-t_1)} + e^{-2\lambda(t_2-t_1)} \qquad (2)$$

where p_1 and p_2 are defined in statement 3 above. If the result obtained is greater than zero, we select one battery from among the $N - n_1$ completely untested batteries and test it at time t_2; if the result obtained is less than or equal to zero, we test at t_2 a battery chosen from among the $n_1 - f_1$ batteries that survived the test at time t_1. We incorporate this new result in the original sample and obtain an adjusted likelihood. With

this likelihood and the original prior we again compute the posterior mean of (2) in order to decide from which set (a) or (b) the next battery will be selected. This procedure will be followed sequentially to complete the sample of size n_2 or until either sets (a) or (b) are exhausted; in this case complete the sample (of size n_2) with items chosen from the remainder set (either (a) or (b)).

To specify the computations explicitly we list the following notation:

n_1 = number of batteries tested at time t_1.

f_1 = number of batteries (among these n_1) failed at time t_1.

n_{12} = number of batteries tested at time t_1 <u>and</u> at time t_2.

f_{12} = number of batteries failed at time t_2 from among these n_{12}.

n_2 = number of batteries tested at time t_2.

f_2 = number of failures among the $n_2 - n_{12}$ batteries tested only at time t_2. (Note that the f_{12} batteries are not part of the f_2 batteries.)

For reasons of simplification we relax the above notation in the following formulas. The quantities n_2, n_{12}, f_2, and f_{12} are viewed below as changing steadily at each step of the sequential procedure.

The general likelihood is given by:

$$L = (e^{-\lambda t_1})^{n_1 - n_{12} - f_1} (1 - e^{-\lambda t_1})^{f_1} (e^{-\lambda t_2})^{n_2 - f_2 - f_{12}} (1 - e^{-\lambda t_2})^{f_2}$$
$$\times (e^{-\lambda t_1} - e^{-\lambda t_2})^{f_{12}} \tag{3}$$

We emphasize the fact that this likelihood is computed at each step with the current values of n_2, n_{12}, f_2, and f_{12}.

From the likelihood (3) and the prior (1), we may compute the Bayes estimator for $e^{-\lambda(c_2 t_2 - c_1 t_1)}$, as follows:

$$E\{e^{-\lambda(c_2 t_2 - c_1 t_1)}|Data\} =$$

$$= \frac{1}{A} \sum_{i=0}^{f_1} \sum_{j=0}^{f_2} \sum_{k=0}^{f_{12}} \frac{(-1)^{i+j+k} \binom{f_1}{i} \binom{f_2}{j} \binom{f_{12}}{k}}{[\beta + t_1(n_1 - f_1 + i + k - c_1) + t_2(n_2 - f_2 + f_{12} + j - k + c_2)]^\alpha} , \qquad (4)$$

$$\text{where } A = \sum_i \sum_j \sum_k \frac{(-1)^{i+j+k} \binom{f_1}{i} \binom{f_2}{j} \binom{f_{12}}{k}}{[\beta + t_1(n_1 - f_1 + i + k) + t_2(n_2 - f_2 + f_{12} + j - k)]^\alpha} .$$

Note that the final Bayes estimator for $e^{-\lambda t_2}$ is computed by taking $c_2 = 1$ and $c_1 = 0$ in (4).

We emphasize that the Bayes sequential procedure described above may be only an approximation to the optimal Bayes procedure. We do not know if this procedure, although very intuitive, is the one which minimizes the risk for the squared loss function.

Final Remark:

Note that the criteria used depend only on the values of p_1 and p_2, not on the fact that we have an exponential distribution. This shows the generality of the methods discussed. On the other hand, suppose that q_1, q_2, and $q_3 = 1 - (q_1 + q_2)$ are the probabilities of a battery failing respectively, before t_1, in the interval (t_1, t_2), and after t_2. If we represent our prior opinion about (q_1, q_2, q_3) by a Dirichlet distribution, then the Bayes solution in this case is very similar to the one presented here.